

## CLAIMS

What is claimed is:

- 1 1. A server-based network presence and location agent which acquires presence  
2 and location information about a plurality of mobile devices operating on a  
3 wireless network from an entity on the wireless network other than the mobile  
4 devices, and which provides the acquired presence and location information to  
5 remote applications which use said information on a computer network.
- 1 2. A server-based network presence and location agent as recited in claim 1,  
2 wherein the network presence and location agent is configured to acquire the  
3 presence and location information in response to requests for said information  
4 from one or more of the remote applications.
- 1 3. A server-based network presence and location agent as recited in claim 1,  
2 wherein the network presence and location agent acquires the presence and  
3 location information independently of any requests for said information.
- 1 4. A server-based network presence and location agent as recited in claim 1,  
2 wherein the network presence and location agent receives the presence or  
3 location information in extensible markup language (XML) format using Short  
4 Message Peer to Peer Protocol (SMPP).

1 5. A server-based network presence and location agent as recited in claim 4,  
 2 wherein the network presence and location agent receives the presence or  
 3 location information using Short Message Peer to Peer Protocol (SMPP).

1 6. A server-based network presence and location agent as recited in claim 4,  
 2 wherein the network presence and location agent provides the presence or  
 3 location information to the remote applications in extensible markup language  
 4 (XML) format using Hypertext Transport Protocol (HTTP).

1 7. A mobile network presence and location agent comprising:  
 2 a pull agent to receive a request from a remote application for presence or  
 3 location information about a mobile device operating on a wireless network, and  
 4 to send a corresponding request for the presence or location information to a  
 5 Short Message Service Center (SMSC), such that the SMSC responds by querying  
 6 a Home Location Register (HLR) of the wireless network to obtain the requested  
 7 presence or location information, wherein the SMSC responds by providing the  
 8 presence or location information to the pull agent, and wherein the pull agent  
 9 subsequently provides the presence or location information to the remote  
 10 application; and

11 a push agent to receive location or presence information about a mobile  
 12 device operating on the wireless network from the HLR, wherein the presence or  
 13 location information received by the push agent is not in response to a specific

14 request for said information, and wherein the push agent subsequently provides  
15 the presence or location information to a remote application.

1 8. A mobile network presence and location agent as recited in claim 7, wherein  
2 the SMSC provides the presence or location information to the pull agent in  
3 extensible markup language (XML) format using Short Message Peer to Peer  
4 Protocol (SMPP).

1 9. A mobile network presence and location agent as recited in claim 7, wherein  
2 the pull agent subsequently provides the presence or location information to the  
3 remote application in XML format using Hypertext Transport Protocol (HTTP).

1 10. A mobile network presence and location agent as recited in claim 7, wherein:  
2 the SMSC provides the presence or location information to the pull agent  
3 in extensible markup language (XML) format using Short Message Peer to Peer  
4 Protocol (SMPP); and  
5 the pull agent subsequently provides the presence or location information  
6 to the remote application in XML format using Hypertext Transport Protocol  
7 (HTTP).

1 11. A mobile network presence and location agent as recited in claim 10, wherein  
2 the push agent provides the presence or location information to a remote  
3 application on the computer network in XML format using HTTP.

1 12. A mobile network presence and location agent as recited in claim 7, wherein  
2 the push agent communicates with the HLR according to J-STD-025.

1 13. A mobile network presence and location agent as recited in claim 7, further  
2 comprising a Session Initiation Protocol (SIP) agent to receive location or  
3 presence information about a processing device on a network from an SIP server,  
4 and to send the location or presence information about the processing device to a  
5 remote application on the computer network.

1 14. A mobile network presence and location agent as recited in claim 13, wherein  
2 the SIP agent sends the location or presence information to the remote  
3 application in XML format using Hypertext Transport Protocol (HTTP).

1 15. A mobile network presence and location agent as recited in claim 13, wherein  
2 the processing device is on an Internet Protocol (IP) based network.

1 16. A mobile network presence and location agent comprising:  
2 a pull agent to receive a request for presence or location information about  
3 a mobile device from a remote application over a computer network, and to send  
4 a corresponding request for the presence or location information to a Short  
5 Message Service Center (SMSC), such that the SMSC responds by querying a  
6 Home Location Register (HLR) of a wireless network on which the mobile device  
7 operates to obtain the requested presence or location information, wherein the  
8 SMSC provides the presence or location information to the pull agent in

9 extensible markup language (XML) format using Short Message Peer to Peer  
10 Protocol (SMPP), and wherein the pull agent subsequently provides the presence  
11 or location information to the remote application in extensible markup language  
12 (XML) format over the computer network using Hypertext Transport Protocol  
13 (HTTP), the presence or location information for use by the remote application;  
14 and

15 a push agent to receive location or presence information about a mobile  
16 device operating on the wireless network from the HLR, wherein the presence or  
17 location information received by the push agent is not in response to a specific  
18 request for said information, and wherein the push agent subsequently provides  
19 the presence or location information to a remote application over the computer  
20 network in XML format using HTTP.

1 17. A mobile network presence and location agent as recited in claim 16, further  
2 comprising a Session Initiation Protocol (SIP) agent to receive location or  
3 presence information about a processing device on an Internet Protocol (IP)  
4 based network from an SIP server, and to send the location or presence  
5 information about the processing device to a remote application in XML format  
6 using SMPP.

1 18. A mobile network presence and location agent as recited in claim 16, wherein  
2 the push agent communicates with the HLR according to J-STD-025.

1 19. A processing system comprising:

2 a processor;

3 a communications interface by which to communicate on a computer  
4 network;

5 a communications interface by which to communicate with a Short  
6 Message Service Center (SMSC); and

7 a storage facility storing instructions for execution by the processor, which  
8 instructions configure the processing system to:

9 receive a request for presence or location information about a  
10 mobile device operating on a wireless network from a remote application over a  
11 computer network;

12 send a corresponding request for the presence or location  
13 information to the SMSC, to cause the SMSC to query a Home Location Register  
14 (HLR) of the wireless network to obtain the requested presence or location  
15 information, wherein the presence or location information is received from the  
16 SMSC in extensible markup language (XML) format using Short Message Peer to  
17 Peer Protocol (SMPP); and

18 provide the received presence or location information to the remote  
19 application in XML format using Hypertext Transport Protocol (HTTP) over the  
20 computer network, the presence or location information for use by the remote  
21 application.



9 a pull agent to receive a request from a remote application for presence or  
10 location information about a mobile device operating on a wireless network, and  
11 to send a corresponding request for the presence or location information to a  
12 remote entity on the wireless network, wherein the remote entity is not any of  
13 the mobile devices, wherein the remote entity responds by providing the  
14 presence or location information to the pull agent, and wherein the pull agent  
15 subsequently provides the presence or location information to the remote  
16 application.

1 23. A gateway server as recited in claim 22, wherein the remote entity is a Home  
2 Location Register (HLR) of the wireless network.

1 24. A gateway server as recited in claim 23, wherein the pull agent receives the  
2 information via a Short Message Service Center (SMSC).

1 25. A gateway server as recited in claim 24, wherein the SMSC provides the  
2 presence or location information to the pull agent in extensible markup language  
3 (XML) format using Short Message Peer to Peer Protocol (SMPP).

1 26. A gateway server as recited in claim 25, wherein the pull agent subsequently  
2 provides the presence or location information to the remote application in XML  
3 format using Hypertext Transport Protocol (HTTP).



1 27. A gateway server as recited in claim 22, further comprising a push agent to  
2 receive location or presence information about a mobile device operating on the  
3 wireless network from the remote entity, wherein the presence or location  
4 information received by the push agent is not in response to a specific request for  
5 said information, and wherein the push agent subsequently provides the  
6 presence or location information to a remote application.

1 28. A gateway server as recited in claim 27, wherein the push agent  
2 communicates with the remote entity according to J-STD-025.

1 29. A gateway server as recited in claim 28, wherein the push agent provides the  
2 presence or location information to a remote application on the computer  
3 network in extensible markup language (XML) format using HTTP.

1 30. A gateway server as recited in claim 22, further comprising a Session  
2 Initiation Protocol (SIP) agent to receive location or presence information about a  
3 processing device on a network from an SIP server, and to send the location or  
4 presence information about the processing device to a remote application on the  
5 computer network.

1 31. A gateway server as recited in claim 30, wherein the SIP agent sends the  
2 location or presence information to the remote application in extensible markup  
3 language (XML) format using Hypertext Transport Protocol (HTTP).

1 32. A gateway server as recited in claim 31, wherein the processing device is on  
2 an Internet Protocol (IP) based network.

1 33. An apparatus for providing an application with location and presence  
2 information about a mobile device operating on a wireless network, the method  
3 comprising:

4 means for receiving presence or location information about the mobile  
5 device from a remote entity; and

6 means for sending the received presence or location information to a  
7 remote application in extensible markup language (XML) format using  
8 Hypertext Transport Protocol (HTTP).

1 34. An apparatus as recited in claim 33, wherein said means for receiving the  
2 presence or location information comprises means for receiving the presence or  
3 location information in an XML format using Short Message Peer to Peer  
4 Protocol (SMPP).

1 35. An apparatus as recited in claim 34, wherein said means for receiving the  
2 presence or location information comprises means for receiving the presence or  
3 location information from a Short Message Service Center (SMSC).

1 36. An apparatus as recited in claim 33, wherein said means for receiving the  
2 presence or location information comprises means for receiving the presence or

3 location information from a Home Location Register (HLR) of the wireless  
4 network.

1 37. An apparatus as recited in claim 33, wherein said means for receiving the  
2 presence or location information comprises means for receiving the presence or  
3 location information from a Session Initiation Protocol (SIP) server by using SIP.

1 38. An apparatus as recited in claim 33, wherein said means for receiving the  
2 presence or location information comprises means for receiving the presence or  
3 location information from a General Packet Radio Service (GPRS) server.

1 39. An apparatus as recited in claim 33, wherein the presence or location  
2 information can be received in response to a request for the presence or location  
3 information previously transmitted to the remote entity.

1 40. An apparatus as recited in claim 39, wherein the request for the presence or  
2 location information is in response to a prior request from a remote application  
3 requiring said information.

1 41. An apparatus as recited in claim 33, further comprising means for pushing  
2 the presence or location information to the remote application independent of  
3 any request for said information.

1 42. An apparatus as recited in claim 41, wherein the presence or location  
2 information is pushed to the remote application in a manner compliant with J-  
3 STD-025.

1 43. A method of providing an application with location and presence  
2 information about a mobile device operating on a wireless network, the method  
3 comprising:  
4 receiving presence or location information about the mobile device from a  
5 remote entity; and  
6 in response to receiving the presence or location information, sending the  
7 presence or location information to a remote application in extensible markup  
8 language (XML) format using Hypertext Transport Protocol (HTTP).

1 44. A method as recited in claim 43, wherein said receiving the presence or  
2 location information comprises receiving the presence or location information in  
3 an XML format using Short Message Peer to Peer Protocol (SMPP).

1 45. A method as recited in claim 44, wherein said receiving the presence or  
2 location information comprises receiving the presence or location information  
3 from a Short Message Service Center (SMSC).

1 46. A method as recited in claim 43, wherein said receiving the presence or  
2 location information comprises receiving the presence or location information  
3 from a Home Location Register (HLR) of the wireless network.

1 47. A method as recited in claim 43, wherein said receiving the presence or  
2 location information comprises receiving the presence or location information  
3 from a Session Initiation Protocol (SIP) server by using SIP.

1 48. A method as recited in claim 43, wherein said receiving the presence or  
2 location information comprises receiving the presence or location information  
3 from a General Packet Radio Service (GPRS) server.

1 49. A method as recited in claim 43, wherein the presence or location  
2 information can be received in response to a request for the presence or location  
3 information previously transmitted to the remote entity.

1 50. A method as recited in claim 49, wherein the request for the presence or  
2 location information is in response to a prior request from a remote application  
3 requiring said information.

1 51. A method as recited in claim 43, wherein the presence or location  
2 information is received as push information, not in response to a specific request.

1 52. A method as recited in claim 51, wherein the presence or location  
2 information is received as push information in a manner compliant with J-STD-  
3 025.

1 53. A method of providing an application on a computer network with location  
2 and presence information about a mobile device operating on a wireless  
3 network, the method comprising:  
4 receiving a first request for presence or location information from an  
5 application over the computer network;  
6 in response to the request, sending a second request corresponding to the  
7 first request to a Short Message Service Center (SMSC), the SMSC obtaining the  
8 requested information in response to the second request by querying a Home  
9 Location Register (HLR) of the wireless network;  
10 receiving the requested information from the SMSC;  
11 in response to receiving the requested information from the SMSC,  
12 sending the requested information to the application over the computer network.

1 54. A method as recited in claim 53, wherein said receiving the requested  
2 information from the SMSC comprises receiving the requested information in  
3 extensible markup language (XML) format using Short Message Peer to Peer  
4 Protocol (SMPP).

1 55. A method as recited in claim 54, wherein said sending the requested  
2 information to the application comprises sending the requested information to  
3 the application in XML format by using Hypertext Transport Protocol (HTTP).

1 56. A method of providing an application on a computer network with location  
2 and presence information about a mobile device operating on a wireless  
3 network, the method comprising:  
4 receiving a first request for presence or location information from an  
5 application over the computer network;  
6 in response to the request, sending a second request corresponding to the  
7 first request to a Session Initiation Protocol (SIP) server by using SIP, the SIP  
8 server obtaining the requested information in response to the second request by  
9 using SIP to query a SIP user agent of the processing device;  
10 receiving the requested information from the SIP server by using SIP;  
11 in response to receiving the requested information from the SIP server,  
12 sending the requested information to the application over the computer network.

1 57. A method as recited in claim 56, wherein said sending the requested  
2 information to the application over the computer network comprises sending the  
3 requested information to the application over the computer network in  
4 extensible markup language (XML) format by using Hypertext Transport  
5 Protocol (HTTP).